

E-mail: info@dansand.dk
Tel: +45 8682 5811
Producer: DANSAND A/S, Lervejdal 8B, 8740 Brædstrup

Responsible: Afdelingschef - QHSE, Morten Grundvad
Item number: 499970
Product designation: Washed and sorted quarz sand

Dansand® Fairway sand 0-1 mm

Extend the golf season

Description

DANSAND® Fairway is specially developed for top dressing of fairways. The product has an optimal grain curve and is based exclusively on round-edged silica sand that has been washed clean of clay, fines and organic material. Over time, the addition of DANSAND® Fairway improves the structure of the soil profile, provides higher permeability and improved growth conditions for the plants. The product is an effective way of preventing wet areas on the fairways, thus prolonging the season for golfing.

BENEFITS OF DANSAND® FAIRWAY 0-1 MM

- Pure silica sand with an optimum grain curve
- Prevents wet areas on the fairways, prolonging the season for golfing

Specifications

DECLARATION

Product description: washed and sifted silica sand Product number: 499970

STORAGE

Under cover and with no risk of contamination

DELIVERY



Delivered loose as a bulk item.

Diameter - mm	Passing - w %
3.4	100
2	100
1	98.9
0.5	79
0.25	26.2
0.15	5.6
0.053	0.1

Category	Diameter - mm	Retained W %
Coarse Gravel	> 3.4	0
Fine Gravel	2.0 - 3.4	0
Very Coarse Sand	1.0 - 3.4	1.1
Coarse Sand	0.5 - 1.0	19.9
Medium Sand	0.25 - 0.5	52.8
Fine Sand	0.15 - 0.25	20.6
Very Fine Sand	0.05 - 0.15	5.5

Silt / Clay	< 0.05	0.1
-------------	--------	-----

Humus - weight %	0
------------------	---



Analysis data should be used as guidance only. The raw material is a natural product whose composition may vary.

Manual

APPLICATION

For top dressing of fairways. Distribute with fairway top dresser in an even layer.



Dansand® Fairway sand 0-1 mm

Variants: 499970