

E-mail: info@dansand.dk
Tel: +45 8682 5811

Responsible: Afdelingschef – QHSE, Morten Grundvad
Product designation:

Mikolit®

Pellets with effective swelling ability

Description

Mikolit® B and Mikolit® 300 are 100 % natural well sealing pellets. Mikolit® B is a high grade bentonite with high swelling capacity and pressure, which makes it suitable in both the saturated and unsaturated zone. Mikolit® 300 is a basic sealing material with less swelling capacity than the Mikolit® B, and is suitable for use in the saturated zone.

Mikolit® is available in three grades:

Mikolit® 00 Pellet with moderate swelling for basic plugging

Mikolit® 300/300M The bentonite content ensures a strong swelling and is therefore a suitable sealing product for all applications. Magnitite 300M is added to the product, making it traceable.

Mikolit® B Mikolit® B is a high grade bentonite with high swelling capacity and pressure, which makes it suitable in both the saturated and unsaturated zone.

BENEFITS OF MIKOLIT®

- Easy to use
- Ensures tight sealing
- High swelling capacity
- Clay-based for zero dust

Specifications

DECLARATION

100 % natural well sealing pellets

STORAGE

Dry, covered and without risk of contamination.

DELIVERY

20 kg bags.

ENVIRONMENTAL INFORMATION AND DISPOSAL

Packaging and used material should be disposed of in accordance with local requirements.

Manual

APPLICATION

Mikolit® is used for the sealing and decommissioning of wells.

DOWNLOADS

- [Mikolit data sheet](#)
- [Mikolit product specification](#)



Mikolit®

Variants: