

E-mail: Tel: info@dansand.dk +45 8682 5811 Responsible: Product designation:

Afdelingschef - QHSE, Morten Grundvad

### Mikolit®

# Pellets with effective swelling ability

## Description

Mikolit® B and Mikolit® 300 are 100 % natural well sealing pellets. Mikolit® B is a high grade bentonite with high swelling capacity and pressure, which makes it suitable in both the saturated and unsaturated zone. Mikolit® 300 is a basic sealing material with less swelling capacity than the Mikolit® B, and is suitable for use in the saturated zone.

Mikolit<sup>®</sup> is available in three grades:

**Mikolit® 00** Pellet with moderate swelling for basic plugging

**Mikolit® 300/300M** The bentonite content ensures a strong swelling and is therefore a suitable sealing product for all applications. Magnitite 300M is added to the product, making it traceable.

**Mikolit** B Mikolit B is a high grade bentonite with high swelling capacity and pressure, which makes it suitable in both the saturated and unsaturated zone.

## Specifications

#### **DECLARATION**

100 % natural well sealing pellets

#### **STORAGE**

Dry, covered and without risk of contamination.

#### BENEFITS OF MIKOLIT®

- · Easy to use
- · Ensures tight sealing
- High swelling capacity
- Clay-based for zero dust

**DELIVERY** 

20 kg bags.

#### **ENVIRONMENTAL INFORMATION AND DISPOSAL**

Packaging and used material should be disposed of in accordance with local requirements.

15.11.25 Page: 1



## Manual

#### **APPLICATION**

 $\mathsf{Mikolit}^{\circledast}$  is used for the sealing and decommissioning of wells.



#### **DOWNLOADS**

- Mikolit data sheet
- Mikolit product specification

Mikolit®

Variants:

15.11.25 Page: 2