

E-mail: info@dansand.dk  
Tel: +45 8682 5811

Responsible: Afdelingschef – QHSE, Morten Grundvad  
Product designation:

## Mikolit®

# Pellets with effective swelling ability

## Description

Mikolit® B and Mikolit® 300 are 100 % natural well sealing pellets. Mikolit® B is a high grade bentonite with high swelling capacity and pressure, which makes it suitable in both the saturated and unsaturated zone. Mikolit® 300 is a basic sealing material with less swelling capacity than the Mikolit® B, and is suitable for use in the saturated zone.

Mikolit® is available in three grades:

**Mikolit® 00** Pellet with moderate swelling for basic plugging

**Mikolit® 300/300M** The bentonite content ensures a strong swelling and is therefore a suitable sealing product for all applications. Magnitite 300M is added to the product, making it traceable.

**Mikolit® B** Mikolit® B is a high grade bentonite with high swelling capacity and pressure, which makes it suitable in both the saturated and unsaturated zone.

## Specifications

### DECLARATION

100 % natural well sealing pellets

### STORAGE

Dry, covered and without risk of contamination.

### BENEFITS OF MIKOLIT®

- Easy to use
- Ensures tight sealing
- High swelling capacity
- Clay-based for zero dust

### DELIVERY

20 kg bags.

### ENVIRONMENTAL INFORMATION AND DISPOSAL

Packaging and used material should be disposed of in accordance with local requirements.

# Manual

## APPLICATION

Mikolit® is used for the sealing and decommissioning of wells.

## DOWNLOADS

- [Mikolit data sheet](#)
- [Mikolit product specification](#)



Mikolit®

Variants: